Revised by: Simonne Moses - HSNO Consultant SDS No: 1

Safety Data Sheet Gum N Tar

Classified as: Hazardous according to the EPA Hazardous Substances (Hazard Classifications) Notice 2020.

Section 1: SUBSTANCE AND SUPPLIER DETAILS

Product Name: Gum N Tar

Supplier: PureWax Ltd

Unit 14, 88 Hobsonville Road

Hobsonville

Auckland 0618

New Zealand

Phone: 0800 PUREWX (787 399)

Recommended Use: Gum and tar remover

In Case of Emergency Contact:

CHEMCALL: 0800 CHEMCALL (243 622)

Section 2: HAZARDS IDENTIFICATION

This product is classified as a Dangerous Good for Transport.

This product is classified as hazardous according to criteria in the EPA Hazardous Substances (Hazard Classifications) Notice 2020.

HSNO APPROVAL NUMBER: HSR002528

HSNO CLASSIFICATIONS: 3.1C Flammable liquid

6.1D Acute toxicity, oral6.1D Acute toxicity, dermal6.1E Aspiration hazard6.3A Skin irritant

6.4A Eye irritant

6.8B Suspected of damaging fertility or the unborn child

6.9B Harmful to human target organs or systems, repeated exposure

GHS Classification: Flammable liquid – Category 3

Acute toxicity, oral – Category 4 Acute toxicity, dermal – Category 4

Skin irritation – Category 2 Eye irritation – Category 2

Reproductive toxicity - Category 2

Specific target organ toxicity, repeated exposure - Category 2

Aspiration hazard - Category 1

Revised by: Simonne Moses - HSNO Consultant SDS No: 1

Hazard Statements: H226 Flammable liquid and vapour

H302 Harmful if swallowed

H304 May be fatal if swallowed and enters airways

H312 Harmful in contact with skin H315 Causes skin irritation H319 Causes serious eye irritation

H361 Suspected of damaging fertility or the unborn child

H373 May cause damage to organs (central nervous system) through prolonged or

repeated exposure via inhalation.

GHS Pictograms:



DANGER

PREVENTION STATEMENTS:

P201 – Obtain special instructions before use.

P202 - Do not handle until all safety instructions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 – Use explosion-proof equipment.

P242 - Use non-sparking tools.

P243 – Take action to prevent static discharges.

P260 – Do not breathe spray/vapours/fumes/mist.

P264 - Wash hands, exposed skin, thoroughly after handling.

P270 - Do not eat, drink, or smoke, when using this product.

P280 - Wear protective gloves, protective clothing, eye protection, face protection.

RESPONSE STATEMENTS:

P301 + P310 – IF SWALLOWED: Immediately call a POISON CENTRE or doctor.

P330 – Rinse mouth.

P331 – Do NOT induce vomiting.

P303 + P361 + P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P321 - Specific treatment (refer to first aid instructions on label).

P363 – Wash contaminated clothing before reuse.

P305 + P351 + P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P337 + P308 + P313 – If skin irritation occurs, or eye irritation persists, or if exposed or concerned: Get medical advice/attention.

P370 + P378 – In case of fire: Use water fog, foam, dry chemical, or carbon dioxide to extinguish.

STORAGE:

P405 – Store locked up.

P403 + P235 - Store in a well-ventilated place. Keep cool.

DISPOSAL:

P501 - In accordance with the EPA Hazardous Substances (Disposal) Notice 2017. Do not incinerate. Dispose of via an approved waste disposal contractor. Refer to Section 13 of the SDS.

Gum N Tar REV 1 Page 2 of 8

Revised by: Simonne Moses - HSNO Consultant SDS No: 1

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Mixture: Gum and tar remover

Main Component	CAS Number	Concentration (% wt)
Petroleum distillates (VP=0.01mmHg @ 20°C)	64742-47-8	55 - 65%
Xylene	1330-20-7	25 - 35%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4: FIRST AID MEASURES

Workplace Facilities

Required:

Shower and eyewash facilities should be provided.

If Inhaled: Remove to fresh air. Seek medical attention if drowsiness or dizziness occurs.

In Contact with Eye: Hold eyes open, flush with water for at least 15 minutes. Seek medical attention if

irritation develops and persists.

In Contact with Skin: Wash skin with plenty of water. Seek medical attention if skin irritation develops and

persists.

If Swallowed: DO NOT INDUCE VOMITING, Seek immediate medical attention, Rinse mouth. If

vomiting occurs, keep head below hips to prevent aspiration to lungs.

Advice to Doctor: Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Fire/Explosion Hazard: Flammable liquid and vapour. Fire-heated containers may become pressurised and

burst.

Suitable Extinguishing

Media:

Use water fog, foam, carbon dioxide, or powder to extinguish. Do not use water jet

as this will spread the fire.

Precautions in Connection

with Fire:

Containers may rupture when heated. Thermal decomposition may produce toxic

fumes containing oxides of carbon and other toxic gases.

Advice for firefighters: Remove containers from path of fire if safe to do so. Cool fire-exposed containers

with water spray. Wear full firefighting gear and self-contained breathing apparatus.

Avoid breathing fumes.

Revised by: Simonne Moses - HSNO Consultant SDS No: 1

Section 6: ACCIDENTAL RELEASE MEASURES

An emergency response plan complying with Part 5 of the Health and Safety at Work (Hazardous Substances) Regulations 2017 is required when guantities exceed 1,000L.

Precautions: Clear area of all unprotected personnel. Keep unnecessary and unprotected

personnel from entering area. Remove all ignition sources. Avoid breathing

vapours, mist, spray. Avoid contact with skin and eyes.

Suitable Protective Equipment: Emergency responders must use personal protective equipment, including respiratory protection, gloves, protective clothing, and safety glasses with side

shields or safety goggles.

Spill or Leak Procedures. Stop leak if safe to do so. Absorb with inert, non-combustible material such as

sand, earth. Clean up using non-sparking tools. Place contaminated absorbent

material in a labelled waste container for disposal.

Waste Disposal Methods: Dispose of as per Section 13.

Emergency preparation: Ensure there is appropriate and adequate personal protective equipment, trained

personnel and clean up materials for management of accidental release.

Section 7: HANDLING AND STORAGE

Precautions for Safe

Handling:

Avoid contact with skin and eyes. Do not breathe vapours, fumes, mist, spray. Use in a well-ventilated area or outdoors. Do not use near ignition sources or hot surfaces. Ground/bond container to prevent build-up of static electricity. Do not eat, drink, or smoke, when using this product. Remove contaminated clothing

and wash hands and face before entering eating areas.

Storage: Store locked up. Keep out of direct sunlight. Keep away from ignition sources

and combustible materials. Store in a well-ventilated area. Do not store near

food, drink, or animal feed. Do not store in unlabelled containers.

Site Storage Requirements: Site Signage will be required when quantities exceed 1,000L.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace Exposure Standards NZ:

No Workplace Exposure Standards have been established for this product but

have been established for the following ingredient:

Xylene – TWA 50 ppm, 217 mg/m³ (ototoxic)

Engineering Controls: Eyewash facilities and safety showers should be provided in the work area where

there is a risk of exposure to eyes and skin. If use results in exposure to vapours, fumes, mist, or spray, use engineering controls such as local exhaust ventilation to ensure workers are not exposed to concentrations that exceed workplace

exposure standards.

Personal Protective

Equipment:

Avoid contact with the skin and eyes. Avoid inhaling vapours, fumes, mist, spray.

Observe good chemical hygiene practice.

Hand protection: Wear protective gloves. Refer to Australian and New Zealand Standard AS/NZS

2161 for protective gloves.

Gum N Tar REV 1 Page 4 of 8

Simonne Moses - HSNO Consultant Revised by: SDS No: 1

Skin and body protection: Wear protective clothing. Refer to Australian and New Zealand Standard AS/NZS

4501 for occupational protective clothing.

Eye protection: Use safety glasses with side shields or safety goggles. Refer to AS/NZS 1336 for

suitable eye and face protection.

Where there is inadequate ventilation, and use results in exposure to vapours, Respiratory protection:

fumes, mist, spray, use a respirator fitted with a solvent vapour cartridge. Refer to

Viscosity (40°C):

Not available

AS/NZS 1715 and AS/NZS 1716 for suitable respiratory protection.

Other information: Handle in accordance with safe industrial hygiene practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Description: Liquid Colour: Colourless Odour: Solvent Odour Threshold: Not available Solubility (water, 20°C): Insoluble pH: Freezing point: Not available **Boiling Point:** >100°C

Flammability: Flammable Flash Point: 37°C (approx.)

LEL/UEL: 0.9 - 7% (estimated) Vapour Pressure (20°C): > 1

Decomposition Temp: Not available **Autoignition Temp:** Not available

Relative Density: Vapour Density: 0.85 (water = 1) > 1

Partition Coefficient: n-

octanol/water

Particle

characteristics:

Not available

Not applicable

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions.

No dangerous reactions are expected to occur under normal storage and use Reactivity:

conditions.

Conditions to Avoid: Heat, sparks, ignition sources, sunlight.

Incompatibility: Strong oxidisers, acids, combustible materials such as wood, paper, cardboard.

Thermal decomposition may result in toxic gases being released including oxides **Hazardous Decomposition:**

of carbon and other toxic gases.

Section 11: TOXICOLOGICAL INFORMATION

Acute Exposure

Acute Toxicity: LD50 oral > 300 - 2000 mg/kg.

> LD50 dermal > 1000 - 2000 mg/kg LC₅₀ inhalation (mist/spray) > 5.0 mg/L

Gum N Tar REV₁ Page 5 of 8

Revised by: Simonne Moses - HSNO Consultant SDS No: 1

Inhalation: Not expected to cause toxic effects or be a respiratory irritant. Inhaling large

quantities may cause drowsiness, dizziness.

Ingestion: Aspiration hazard. May be fatal if swallowed and enters airways. Harmful if

swallowed.

Skin Contact: Harmful in contact with skin. Skin irritant.

Eye Contact: Eye irritant.

Sensitiser: Not expected to be a respiratory or contact sensitiser.

Chronic Exposure:

Mutagen/Carcinogen/Reproductive

Toxicant

Product is a suspected reproductive toxicant. Not expected to be mutagenic or

carcinogenic.

Specific Target Organ Systemic

. Toxicity: Product is harmful to human target organs or systems (central nervous system)

via inhalation.

Toxicity data is based on hazardous ingredient information and information in the

EPA Chemical Classification and Identification Database.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Product is not expected to be ecotoxic.

Persistence/degradability: Not available.

Bioaccumulation: Not available.

Mobility: Product is insoluble in water.

Ecotoxicity data is based on hazardous ingredient information.

Section 13: DISPOSAL CONSIDERATIONS

Disposal: Recycle and reuse wherever possible. Dispose of waste product via an approved

waste disposal contractor.

Disposal of Packaging: Dispose of packaging via an approved waste disposal contractor.

Section 14: TRANSPORT INFORMATION

This product is classified as a Dangerous Good for transport in accordance with NZS5433:2020, IMDG or IATA.

Gum N Tar REV 1 Page 6 of 8

Revised by: Simonne Moses - HSNO Consultant SDS No: 1



NZS5433:2020 UN No: 1993

Proper Shipping Name: Flammable liquid n.o.s. (contains Xylene)

Class: 3

Packing Group: III

Environmentally hazardous: No

Hazchem Code: 3YE

IMDG:

UN No: 1993

Proper Shipping Name: Flammable liquid n.o.s. (contains Xylene)

Class: 3

Packing Group: III Marine Pollutant: No EmS: F-E. S-E

IATA:

UN No: 1993

Proper Shipping Name: Flammable liquid n.o.s. (contains Xylene)

Class: 3

Packing Group: III

Ensure transportation methods prevent leakage from packages and collapsing loads.

Section 15: REGULATORY INFORMATION

Group Standard Allocation: Cleaning Products (Flammable) Group Standard 2020

HSNO Approval Code: HSR002528

Classifications: Flammable liquid – Category 3

Acute toxicity, oral – Category 4 Acute toxicity, dermal – Category 4

Skin irritation – Category 2 Eye irritation – Category 2

Reproductive toxicity - Category 2

Specific target organ toxicity, repeated exposure - Category 2

Aspiration hazard - Category 1

This substance triggers: Compliance Certificate 500L (containers > 5L), 1,500L (containers

up to 5L)

Certified Handler N/A
Quantity that must be secured N/A
Emergency Response Plan 1,000L
Secondary Containment 1,000L

Revised by: Simonne Moses - HSNO Consultant SDS No: 1

Signage 1,000L

Fire Extinguishers 2 required for quantities > 500L

This substance is not required to be Tracked. All workplace personnel handling this substance are required to be trained on the safe handling and PPE requirements for the hazards associated with this substance.

Section 16: OTHER INFORMATION

The information provided in this Safety Data Sheet relates only to the specific material designated herein. This Safety Data Sheet summarises our best knowledge of the health and safety hazard information of the product and how to safely handle the product in the workplace. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products.

This substance is approved for use as a cleaning product. All reasonable care has been taken to ensure that the information and advice contained herein are from sources believed to be reliable and to represent the most up-to-date knowledge available at the date given in Section 16. No liability is assumed for any damages related to the use or misuse of this substance.

All chemical materials may present unknown hazards as people have varying degrees of sensitivity to chemicals. Therefore, this product should be used with caution. The information herein is given in good faith, but no warranty, express or implied is made.

SDS Issued: 16 September 2022

Reason for Revision: Update to New Zealand regulatory requirements.

References:

EPA NZ Chemical Classification and Information Database European Chemical Agencies Database EPA Guide: Assigning a Hazardous Substance to a Group Standard, 2014 Supplier SDS: 3D International, USA, Gum Tar Remover, June 2016

END OF SAFETY DATA SHEET

Gum N Tar REV 1 Page 8 of 8